

LU LINKABLE BATTEN

BETTER LIGHTING - BETTER PERFORMANCE



LINKABLE DESIGN (42 METERS - SINGLE PHASE)



130 LM P/WATT



COST-EFFECTIVE

EASY TO INSTALL

...

LINK-ABLE DESIGN

...

SIGNIFICANT
ENERGY SAVINGS

HIGH-QUALITY

3 YEAR WARRANTY

...

SUSPENSION MOUNT

...

40,000+ LIFESPAN



GREEN

NO TOXIC WASTE

...

RECYCLABLE

...

RoHS COMPLIANT

SAFE

SHATTER-PROOF

...

NO UV LIGHT

...

LOW SURFACE
TEMPERATURE

DUALCOM TECHNOLOGY LTD

e. info@dualcom.co.nz

p. +64 9 218 5318



DUALCOM
TECHNOLOGY

LU LINKABLE BATTEN

BETTER LIGHTING - BETTER PERFORMANCE



3 YEAR WARRANTY

LIN-LINK1200



SECURE CLIP SYSTEM



SUSPENSION AND LINKING KIT



CLOVER PIN LINK-ABLE DESIGN



Light Source
Power Consumption
Colour Temp (CCT)
Lumen Output
CRI
Beam Angle
IP Protection Rating

288 x SMD2835
40W
5000K
5200Lm (130 LM/W)
>80 CRI
120 degree
IP 42

Overall Dimensions
Construction
Lens Type
Driver Type
Driver Input Voltage
Rated Lifespan
Certifications

1200*73*55mm
6063AL+PC
Frosted / Diffused
Internal
200-240vAC
40,000+ hours
AS/NZS 60598.1:2003
SAA152499, C-Tick, EMC
AS/NZS 60598.2.1:2014
AS/NZS 60598.1:2013
AS/NZS IEC 61347.2.13:2013
AS/NZS 61347.1:2002.



DUALCOM TECHNOLOGY LTD T/A LEDS UNLIMITED

e. info@dualcom.co.nz

p. +64 9 218 5318



DUALCOM
TECHNOLOGY