

LU GEN4 BATTEN

BETTER LIGHTING - BETTER PERFORMANCE



COST-EFFECTIVE

EASY TO INSTALL
...
SURFACE MOUNT
...
WAGO TERMINAL
QUICK CONNECTION

HIGH-QUALITY

3 YEAR WARRANTY
...
AIR GAP PROFILE
...
40,000+ LIFESPAN

GREEN

NO TOXIC WASTE
...
RECYCLABLE
...
RoHS COMPLIANT

SAFE

SHATTER-PROOF
...
NO UV LIGHT
...
LOW SURFACE
TEMPERATURE

DUALCOM TECHNOLOGY LTD
e. info@dualcom.co.nz
p. +64 9 218 5318



DUALCOM
TECHNOLOGY

LU GEN4 BATTEN

BETTER LIGHTING - BETTER PERFORMANCE



3 YEAR WARRANTY

	LIN-G4-600	LIN-G4-1200	LIN-G4-1500
Light Source	144 x SMD2835	288 x SMD2835	432 x SMD2835
Power Consumption	20W	40W	60W
Colour Temp (CCT)	5000K	5000K	5000K
Lumen Output	2400Lm	4800Lm	7200Lm
CRI	>83 CRI	>83 CRI	>83 CRI
Beam Angle	120 degree	120 degree	120 degree
IP Protection Rating	IP 30	IP 30	IP 30
Overall Dimensions	600*80*36mm	1200*80*36mm	1500*80*36mm
Construction	AL+PC	AL+PC	AL+PC
Lens Type	Frosted / Diffused	Frosted / Diffused	Frosted / Diffused
Driver Type	Internal	Internal	Internal
Driver Input Voltage	180-240vAC	180-240vAC	180-240vAC
Rated Lifespan	40,000+ hours	40,000+ hours	40,000+ hours
Certifications	AS/NZS 60598.1:2003 SAA152499, C-Tick, EMC AS/NZS 60598.2.1:2014 AS/NZS 60598.1:2013 AS/NZS IEC 61347.2.13:2013 AS/NZS 61347.1:2002.	AS/NZS 60598.1:2003 SAA152499, C-Tick, EMC AS/NZS 60598.2.1:2014 AS/NZS 60598.1:2013 AS/NZS IEC 61347.2.13:2013 AS/NZS 61347.1:2002.	AS/NZS 60598.1:2003 SAA152499, C-Tick, EMC AS/NZS 60598.2.1:2014 AS/NZS 60598.1:2013 AS/NZS IEC 61347.2.13:2013 AS/NZS 61347.1:2002.



DUALCOM TECHNOLOGY LTD

e. info@dualcom.co.nz

p. +64 9 218 5318



DUALCOM
TECHNOLOGY